



® *Light Engineered Displays, Inc.*

Graphic Annunciators * Water Leak Detection
Fireman's Smoke Control Panels * ARA Systems

109 Portwatch Way Wilmington, N.C. 28412 Phone: (800) 251-2512 Fax: (800) 251-9878
Internet: www.ledinc.com Email: sales@ledinc.com

**HVAC DISCONNECT
SWITCH & EL-1 ELEVATOR
WARNING PLATE**



**HVAC Emergency Disconnect Switch
Model HVAC**

The Emergency Disconnect Switch provides a means to manually disable the HVAC system. The unit is constructed of UL Listed parts with a switch rating of 6 Amps @ 125 VAC.

Durable inks are used in the printing to insure long life, non-fading, and scratch-resistant wording. The word "Emergency" is printed in brilliant red and the words "Air Handler Shut-off" are in black (shown above).

The 2-position maintained aircraft style toggle switch is mounted on a single gang plate. The plate is available in white or stainless steel.



**Do Not Use Elevator Warning Plate
Model EL-1**

The "Do Not Use Elevator" plate provides an effective warning to firefighters NOT to use the elevators even with the bypass key, as a fire has been detected in the elevator mechanical room.

The warning label is silkscreened in Red ink on a single gang stainless steel plate. When activated, a bright red flashing LED draws the firefighters attention to the message.

The indicator is designed for operation at 24VDC using a current draw of 20ma.. The unit has a blocking diode for use on he supervised circuits.